


# Joivy

INTERNATIONAL JOURNAL ON INFORMATICS VISUALIZATION



VOLUME: 1  
NUMBER: 1

Published by  
Information Technology Department  
Politeknik Negeri Padang



[HOME](#) [ABOUT](#) [LOGIN](#) [REGISTER](#) [SEARCH](#) [CURRENT](#) [ARCHIVES](#)

[Home](#) > [About the journal](#) > [Editorial Team](#)

## Editorial Team

### Editor in Chief

Prof. Halimah Badloze Zaman, (Scopus ID: 25825801600); Institute of Visual Informatics, Malaysia  
Rahmat Hidayat, (Scopus ID: 57204348632); Politeknik Negeri Padang, Sumatera Barat, Indonesia

### Regional (Handling) Editor for Europe

Prof. Luca Di Nunzio, (Scopus ID: 57195199010); Università degli Studi di Roma Tor Vergata, Rome, Italy  
Benjamin Duraković, (Scopus ID: 57195199010); International University of Sarajevo, Sarajevo, Bosnia and Herzegovina

### Regional (Handling) Editor for America

Miguel Botto-Tobar, (Scopus ID: 57196152677); Eindhoven University of Technology, Eindhoven, Netherlands  
Santiago Vidal, (Scopus ID: 36142371300); Universidad Nacional del Centro de la Provincia de Buenos Aires, Tandil, Argentina

### Regional (Handling) Editor for Asia-Pacific

Shahreen Kasim, (Scopus ID: 36155431900); Universiti Tun Hussein Onn Malaysia, Batu Pahat, Malaysia  
Hairulnizam Mahdin, (Scopus ID: 35759460000); Universiti Tun Hussein Onn Malaysia, Batu Pahat, Malaysia

### Regional (Handling) Editors for Australia

Vijayakumar Varadarajan, (Scopus ID: 57200993506); University of New South Wales, Sydney, Australia  
Zaini Ismael Rizman, (Scopus ID: 36959761800); Universiti Teknologi MARA, Terengganu, Malaysia

### Regional (Handling) Editor for Middle East and Africa

Prof. Anton S Prabuwo, (Scopus ID: 18134309800); King Abdulaziz University, Jeddah, Saudi Arabia  
Haitham Alali, (Scopus ID: 49963007000); Amman Arab University, Amman, Jordan

### Advisory International Editorial Boards

Prof. Alessandro Simonetta, (Scopus ID: 55344403700) University of Rome "Tor Vergata", Rome, Italy  
Prof. Soundararajan Ezekiel, (Scopus ID: 7003884603); Indiana University of Pennsylvania, Indiana, United States  
Prof. Shahrul Azman Mohd Noah, (Scopus ID: 35087633200); Universiti Kebangsaan Malaysia, Bangi, Malaysia  
Prof. Junzo Watada, (Scopus ID: 57189052014); Zhejiang Gongshang University, Hangzhou, China  
Prof. Gabriele Arcidiacono, (Scopus ID: 56656284600); Università degli Studi Guglielmo Marconi, Rome, Italy  
Prof. Jermal H. Abawajy, (Scopus ID: 8937496700); Deakin University, Geelong, Australia  
Ansari Saleh Ahmar, (Scopus ID: 57203957779); Universitas Negeri Makassar, Indonesia  
Abdullah Ali Alshehri, (Scopus ID: 25638201400); King Abdulaziz University, Jeddah, Saudi Arabia  
Riyanto Sigit, (Scopus ID: 35811196100); Politeknik Elektronika Negeri Surabaya, Jawa Timur, Indonesia  
Guido P. Bakema, (Scopus ID: 15135171300); Hogeschool van Arnhem en Nijmegen, Nijmegen, Netherlands  
Hamid Ali Abed Al Asadi, (Scopus ID: 57202357828); University of Basrah, Basra, Iraq  
Aji Prasetya Wibawa, (Scopus ID: 56012410400); Universitas Negeri Malang, Indonesia, Indonesia

### Managing Editor

Hidra Amnur, (Scopus ID: 57204623296); Politeknik Negeri Padang, Sumatera Barat, Indonesia  
Aide Alanda, (Scopus ID: 57203718850); Politeknik Negeri Padang, Sumatera Barat, Indonesia

### Support Editors :

Aldo Erlanda, (Scopus ID: 57217134570); Politeknik Negeri Padang, Sumatera Barat, Indonesia  
Taufik Gusman, (Scopus ID: 57221394882); Politeknik Negeri Padang, Sumatera Barat, Indonesia

### Technical Editor

[joiv.org/index.php/joiv/about/editorialTeam](http://joiv.org/index.php/joiv/about/editorialTeam)

#### QUICK MENU

[Editorial Team](#)

[Focus & Scope](#)

[Indexing](#)

[Author Guidelines](#)

[Peer Review Process](#)

[Author Fees](#)

[Publication Ethics](#)

[Online Submission](#)

[Open Access Statement](#)

[Plagiarism Policy](#)

[Special Issues](#)

[Licensing terms](#)

[Contact](#)

**1.2** **2021**  
**CiteScore**  
32nd percentile  
Powered by **Scopus**

International Journal on  
Informatics Visualization

**Q4** Computer Science  
(miscellaneous)  
best quartile

**SJR 2022**  
**0.19**  
powered by scimagojr.com

#### REQUEST INDEXING

• **SCOPUS (ACCEPTED)**

- Submission Received: **March 3, 2020**
- Submission Accepted: **July 30, 2020**
- **SCOPUS CiteScore Tracker**

## Vol 7, No 1 (2023)

This issue has been available online since **4th March 2023** for the regular issue of March 2023. All articles in this issue (**35 original research articles**) were authored/co-authored by **131 authors** from **10 countries** (Bangladesh, Indonesia, Laos, Malaysia, Philippines, South Korea, Sweden, Thailand, Taiwan and Vietnam).



## Table of Contents

## Articles

## K-Means Algorithm Analysis for Election Cluster Prediction

*Sri Nugri Walyani ( Universitas Anshom Yogyakarta, Sleman, Yogyakarta 55283, Indonesia)  
Nazman Nizar Khassan ( University of Professionals, Mirpur Cantonment, Dhaka, 1216, Bangladesh)  
Neli Astuti ( Universitas Anshom Yogyakarta, Sleman, Yogyakarta 55283, Indonesia)*

Abstract: 0 Viewers PDF: 0 Viewers DOI: <http://dx.doi.org/10.30630/joiv.7.1.1107>

PDF  
1-6

## Machine Learning Algorithms Based on Sampling Techniques for Raisin Grains Classification

*Achmad Rizki ( Universitas Islam Negeri Sultan Maulana Hasanudin Banten, Serang, Indonesia)  
Muzaffar Man ( Universiti Malaysia Terengganu, Terengganu, Malaysia)*

Abstract: 0 Viewers PDF: 0 Viewers DOI: <http://dx.doi.org/10.30630/joiv.7.1.1190>

PDF  
7-14

## Solar Powered Vibration Propagation Analysis System using nRF2401 based WSN and FRBR

*Birarasa Widanawati ( University of Mataram, Mataram, Indonesia)  
Mada Saiba Yulita ( University of Mataram, Mataram, Indonesia)  
I Wayan Sudarta ( University of Mataram, Mataram, Indonesia)  
I Wayan Agus Arimbasa ( Seoul National University, Seoul, Republic of Korea)  
Tanang Mulyana ( Telkom University, Bandung, Indonesia)*

Abstract: 0 Viewers PDF: 0 Viewers DOI: <http://dx.doi.org/10.30630/joiv.7.1.1592>

PDF  
15-21

## Mapping User Experience Information Overload Problems Across Disciplines

*Wahyu Andhyka Kusuma ( University Putra Malaysia, Malaysia)  
Azrul Huzri Jansen ( University Putra Malaysia, Malaysia)  
Bashir bin Abdullah ( University Putra Malaysia, Malaysia)  
Noris Adooliastoro ( University Putra Malaysia, Malaysia)  
Naris Hani Mohd Namsul ( University Putra Malaysia, Malaysia)*

Abstract: 0 Viewers PDF: 0 Viewers DOI: <http://dx.doi.org/10.30630/joiv.7.1.1588>

PDF  
22-29

## The IT Services Management Architecture Design for Large and Medium-sized Companies based on ITIL 4 and TOGAF Framework

*Iqbal Santosa ( Telkom University, Bandung, Indonesia)  
Rahmat Mulyana ( Stockholm University, Bergsjogatan 12, Kista, 16433, Sweden)*

Abstract: 0 Viewers PDF: 0 Viewers DOI: <http://dx.doi.org/10.30630/joiv.7.1.1590>

PDF  
30-36

## Selecting Control Menu on Electric Wheelchair Using Eyeball Movement for Difable Person

*Fitri Usambingrum ( Brawijaya University, Malang, Indonesia)  
I Komang Sasmita ( National Institute of Technology Malang, Malang, Indonesia)*

PDF  
37-43

Issue Coverage  
(131 Authors)

## Total 10 Author's Countries

<input type="checkbox"/> Bangladesh	(1)
<input type="checkbox"/> Indonesia	(94)
<input type="checkbox"/> South Korea	(2)
<input type="checkbox"/> Laos	(1)
<input type="checkbox"/> Malaysia	(24)
<input type="checkbox"/> Philippines	(1)
<input type="checkbox"/> Sweden	(1)
<input type="checkbox"/> Thailand	(1)
<input type="checkbox"/> Taiwan	(1)
<input type="checkbox"/> Vietnam	(5)

[www.joiv.org](http://www.joiv.org)

## QUICK MENU

Editorial Team

Focus & Scope

Indexing

Author Guidelines

Peer Review Process

Author Fees

Publication Ethics

Online Submission

Open Access Statement

Plagiarism Policy

Special Issues

Licensing terms

Contact

1.2 <sup>2021</sup>  
CiteScore

32nd percentile  
Powered by SCOPUS



HOME ABOUT LOGIN REGISTER SEARCH CURRENT ARCHIVES

Home > Vol 7, No 1 (2023) > Hairani

## Improvement Performance of the Random Forest Method on Unbalanced Diabetes Data Classification Using Smote-Tomek Link

Hairani Hairani - Universitas Bumigora, Mataram, 83127, Indonesia  
Anthony Anggrowan - Universitas Bumigora, Mataram, 83127, Indonesia  
Dodong Prjanto - Universitas Bumigora, Mataram, 83127, Indonesia

Citation Format:

DOI: <http://dx.doi.org/10.30630/joiv.7.1.1069>

### Abstract

Most of the health data contained unbalanced data that affected the performance of the classification method. Unbalanced data causes the classification method to classify the majority data more and ignore the minority class. One of the health data that has unbalanced data is Pima Indian Diabetes. Diabetes is a deadly disease caused by the body's inability to produce enough insulin. Complications of diabetes can cause heart attacks and strokes. Early diagnosis of diabetes is needed to minimize the occurrence of more severe complications. In the diabetes dataset used, there is an imbalanced data between positive and negative diabetes classes. Diabetes negative class data (500 data) is more than diabetes positive class (268), so it can affect the performance of the classification method. Therefore, this study aims to apply the Smote-TomekLink and Random Forest methods in the classification of diabetes. The research methodology used is the collection of diabetes data obtained from Kaggle, as many as 768 data with eight input attributes and 1 output attribute as a class, pre-processing data is used to balance the dataset with Smote-TomekLink, classification using the random forest method, and performance evaluation based on accuracy, sensitivity, precision, and F1-score. Based on the tests conducted by dividing data using 10-fold cross-validation, the Random Forest algorithm with Smote-TomekLink gets the highest accuracy, sensitivity, precision, and F1-score compared to Random Forest with Smote. The Random Forest algorithm with Smote-TomekLink has 86.4% accuracy, 88.2% sensitivity, 82.3% precision, and 85.1% F1-score. Thus, using Smote-TomekLink can improve the performance of the random forest method based on accuracy, sensitivity, precision, and F1-score.

### Keywords

Class Imbalance; Smote-TomekLink; Random Fores Method; Diabetest Disease

### Full Text:

[PDF](#)

### References

- O. Heranova, "Synthetic Minority Oversampling Technique pada Averaged One Dependence Estimators untuk Klasifikasi Credit Scoring", RESTI (Rekayasa Sist. dan Teknol. Informasi), vol. 3, no. 3, pp. 443-450, 2019, doi: 10.29207/resti.v3i3.1275.
- T. Zhu, Y. Lin, and Y. Liu, "Synthetic minority oversampling technique for multiclass imbalance problems," Pattern Recognit., vol. 72, pp. 327-340, Dec. 2017, doi: 10.1016/j.patcog.2017.07.024.
- F. Last, G. Douzas, and F. Bacao, "Oversampling for Imbalanced Learning Based on K-Means and SMOTE," no. November, 2017.
- G. A. Pradipta, R. Wardoyo, A. Musdholifah, and I. N. H. Sanjaya, "Radius-SMOTE: A New Oversampling Technique of Minority Samples Based on Radius Distance for Learning from Imbalanced Data," IEEE Access, vol. 9, pp. 74763-74777, 2021, doi: 10.1109/ACCESS.2021.3088216

### QUICK MENU

- [Editorial Team](#)
- [Focus & Scope](#)
- [Indexing](#)
- [Author Guidelines](#)
- [Peer Review Process](#)
- [Author Fees](#)
- [Publication Ethics](#)
- [Online Submission](#)
- [Open Access Statement](#)
- [Plagiarism Policy](#)
- [Special Issues:](#)
- [Licensing terms](#)
- [Contact](#)

12 <sup>2021</sup> CiteScore  
32nd percentile  
Powered by Scopus

International Journal on Informatics Visualization


Q4 Computer Science (miscellaneous)  
best quartile

SJR 2022  
0.19  
powered by scimagojr.com

### REQUEST INDEXING

- SCOPUS (ACCEPTED)
  - Submission Received: **March 3, 2020**
  - Submission Accepted: **July 30, 2020**
  - SCOPUS CiteScore Tracker 2020
- WoS / Web of Science

**Bukti Kinerja**



## Improvement Performance of the Random Forest Method on Unbalanced Diabetes Data Classification Using Smote-Tomek Link

Hairani Hairani<sup>a,\*</sup>, Anthony Anggrawan<sup>a</sup>, Dadang Priyanto<sup>a</sup>

<sup>a</sup>Department of Computer Science, Universitas Bumigora, Mataram, 83127, Indonesia

Corresponding author: \*hairani@universitasbumigora.ac.id

**Abstract**— Most of the health data contained unbalanced data that affected the performance of the classification method. Unbalanced data causes the classification method to classify the majority data more and ignore the minority class. One of the health data that has unbalanced data is Pima Indian Diabetes. Diabetes is a deadly disease caused by the body's inability to produce enough insulin. Complications of diabetes can cause heart attacks and strokes. Early diagnosis of diabetes is needed to minimize the occurrence of more severe complications. In the diabetes dataset used, there is an imbalanced data between positive and negative diabetes classes. Diabetes negative class data (500 data) is more than diabetes positive class (268), so it can affect the performance of the classification method. Therefore, this study aims to apply the Smote-TomekLink and Random Forest methods in the classification of diabetes. The research methodology used is the collection of diabetes data obtained from Kaggle, as many as 768 data with eight input attributes and 1 output attribute as a class, pre-processing data is used to balance the dataset with Smote-TomekLink, classification using the random forest method, and performance evaluation based on accuracy, sensitivity, precision, and F1-score. Based on the tests conducted by dividing data using 10-fold cross-validation, the Random Forest algorithm with Smote-TomekLink gets the highest accuracy, sensitivity, precision, and F1-score compared to Random Forest with Smote. The Random Forest algorithm with Smote-TomekLink has 86.4% accuracy, 88.2% sensitivity, 82.3% precision, and 85.1% F1-score. Thus, using Smote-TomekLink can improve the performance of the random forest method based on accuracy, sensitivity, precision, and F1-score.

**Keywords**— Class Imbalance; smote-tomekLink; random forest method; diabetes disease.

Manuscript received 1 Aug. 2022; revised 4 Nov. 2022; accepted 13 Dec. 2022. Date of publication 31 Mar. 2023.  
International Journal on Informatics Visualization is licensed under a Creative Commons Attribution-Share Alike 4.0 International License.



### I. INTRODUCTION

Most of the Health data contained unbalanced data that affected the performance of the classification method. Unbalanced data causes the classification method to classify the majority data more and ignore the minority class. One of the health data that has unbalanced data is Pima Indian Diabetes. Diabetes is a deadly disease caused by increased blood sugar in the body. Diabetes is caused by the body's inability to produce enough insulin. Complications of diabetes can cause heart attacks and strokes. One way to improve the performance of the classification method is to manage balanced data by adding minority data so that the number is equal to the majority class. The diabetes dataset has 768 instances of data. However, the problem is an imbalance of data in the dataset, namely the negative diabetes class with 500 data (majority class), while the positive diabetes class with 268 data (minority class). Data imbalance is the amount of data in one class more than in the other class. The problem

of data imbalance causes the classification method to be more dominant in classifying the majority class than the minority class, or in other words, the classification method ignores the minority class. The problem of unbalanced data can be handled with a data sampling approach.

Several data sampling methods that can be used to solve the problem of data imbalance are oversampling [1]–[4], undersampling [5], [6], and Hybrid Sampling [6],[7]. Oversampling works by adding the minority class, while Undersampling works by removing the majority class to produce balanced data. However, both methods have their respective weaknesses. The weakness of the oversampling method is that there are too many repetitions of samples which can cause overfitting of the classification method, while the weakness of undersampling is that it will lose information from most of the samples in the dataset and cannot take full advantage of the available information[9].

The Smote method was developed to overcome these weaknesses to avoid overfitting the oversampling method. Smote is an oversampling method to generate new synthesis

training data by linear interpolation on minority classes[10]. However, the Smote method has a weakness, namely overgeneralization, and the addition of a minority class randomly can generate noise data because it does not differentiate between classes[11]. Therefore, the undersampling method is used to improve the performance of the oversampling method by cleaning the noise data in the majority class. The noise data is the majority class instance which is closest to the minority class instance. Usually, noise data reduces the level of accuracy for classification methods[5]. One method to remove noise data in the majority class is Tomeklink[12]. Tomeklink is an undersampling method that cleans noise data from the majority class, which has similar characteristics and overlapping. However, Tomeklink only deletes instances defined as “Tomek Links” so that the analyzed data cannot be balanced, and in its implementation, the method is combined with other methods. Combining Tomeklink and Smote oversampling can improve accuracy better than individual performance[13].

Data mining research in Health plays an important role, especially in predicting various types of diseases using different techniques or methods[14]. Research [15] uses a statistical approach to analyze the success rate of students following subjects using online or face-to-face learning. The results show that online students have significantly higher average grades than face-to-face classes.

Several previous studies have focused on the classification of diabetes; namely, Kaur [16] predicts diabetes using the k-NN method with an accuracy of 83%. The weakness of the research is that it does not address the problem of data imbalance. Azrar et al. [17] classify diabetes using the C4.5 method with an accuracy of 75.65%. The weakness of the research is that the accuracy obtained is low, so it can be improved, and it does not address the data imbalance problem. Barik et al. [18] Using XGBoost to predict diabetes with 74% accuracy. The weakness of the research is that the accuracy obtained is low, so it can be improved, and it does not address the data imbalance problem.

Hairani, Innuddin, and Rahardi [19] used the Correlated Naïve Bayes method with correlation-based feature selection to predict diabetes with an accuracy of 69.51%. The weakness of the research is that the accuracy obtained is low, so it can be improved, and it does not address the data imbalance problem. Fiarni, Sipayung, and Maemunah [20] used the C4.5 method for diabetes detection with an accuracy of 68%.

Erlin et al. [21] used logistic regression and smote methods to detect diabetes with 82% accuracy, 81% precision, 79% recall, and 80% F1-score. The weakness of the research is that the accuracy is good but can be improved using Tomeklink to clean noise data in the majority class. Azad et al. [22] used the C4.5 and Smote methods to predict diabetes with 82% accuracy, 80% precision, and 86% sensitivity. Shi et al. [23] used logistic and Smote-ENN methods to predict kidney disease with 75.2% accuracy, 70.6% recall, 4.9% precision, and 30% F1-score. The weakness of the research is the low accuracy, so it can be improved using Tomeklink to clean noise data in the majority class. Wang et al. [24] studied SME-XGBoost with Smote-ENN for heart disease prediction with 80% AUC.

Several previous studies have applied various approaches to improve diabetes classification methods, such as the

oversampling approach with SMOTE. However, there are weaknesses in previous studies; namely, the accuracy of the proposed method still ranges from 82% to 83%, so there is a gap in improving its accuracy. So, this study proposes the Smote-Tomeklink hybrid sampling method to overcome the imbalance in diabetes data and improve the accuracy of the classification method.

Smote-Tomeklink is a good way to avoid the drawbacks of SMOTE and Tomeklink techniques [9]. The classification method used in this research is Random Forest. The Random Forest method was chosen because it has several advantages: high accuracy [25], the ability to handle noise data, fast performance in training data, overfitting control, and ease of implementation [26].

This study aims to apply the Smote-Tomeklink hybrid sampling method to balance the data on diabetes data so as to improve the performance of the Random Forest classification method. Measurement of the performance of the random forest method based on accuracy, sensitivity (recall), precision, and F1-score

## II. MATERIALS AND METHOD

This research consists of several stages, as shown in Figure 1.




Fig. 1 Research Stages

### A. Data Collection

The dataset used in this study is a diabetes dataset obtained from Kaggle, which consists of 768 instances and 9 attributes. The description of the attributes and the sample data used are shown respectively in Table I and Table II.

TABLE I  
DESCRIPTION ATRIBUT DATASET

No	Attribute	Description	Label
1	Pregnancies	Number of Pregnancy	X1
2	Glucose	Glucose level 2 hours after eating	X2
3	Blood Pressure	Blood Pressure	X3
4	Skin Thickness	Skin Thickness	X4
5	Insulin	Insulin	X5
6	BMI	Body Massa Index	X6
7	Diabetes Pedigree Function	Diabetes Pedigree Function	X7
8	Age	Age	X8
9	Outcome	Diabetes Status (1 = Positive Diabetes, 2 = Negative Diabetes)	Y

TABLE III  
SAMPLE DATASET

No	X1	X2	X3	X4	X5	X6	X7	X8	Y
1	6	148	72	35	0	33.6	0.627	50	1
2	1	85	66	29	0	26.6	0.351	31	0
3	8	183	64	0	0	23.3	0.672	32	1
4	1	89	66	23	94	28.1	0.167	21	0
5	0	137	40	35	168	43.1	2.288	33	1
6	5	116	74	0	0	25.6	0.201	30	1
7	3	78	50	32	88	31	0.248	26	1
8	10	115	0	0	0	35.3	0.134	29	0
9	2	197	70	45	543	30.5	0.158	53	1
10	8	125	96	0	0	0	0.232	54	1
11	4	110	92	0	0	37.6	0.191	30	0
12	10	168	74	0	0	38	0.537	34	1
13	10	139	80	0	0	27.1	1.441	57	0
14	1	189	60	23	846	30.1	0.398	59	1
15	5	166	72	19	175	25.8	0.587	51	1
..	..	...	..	..	...	..	.....	..	..
754	0	181	88	44	510	43.3	0.222	26	1
755	8	154	78	32	0	32.4	0.443	45	1
756	1	128	88	39	110	36.5	1.057	37	1
757	7	137	90	41	0	32	0.391	39	0
758	0	123	72	0	0	36.3	0.258	52	1
759	1	106	76	0	0	37.5	0.197	26	0
760	6	190	92	0	0	35.5	0.278	66	1
761	2	88	58	26	16	28.4	0.766	22	0
762	9	170	74	31	0	44	0.403	43	1
763	9	89	62	0	0	22.5	0.142	33	0
764	10	101	76	48	180	32.9	0.171	63	0
765	2	122	70	27	0	36.8	0.34	27	0
766	5	121	72	23	112	26.2	0.245	30	0
767	1	126	60	0	0	30.1	0.349	47	1
768	1	93	70	31	0	30.4	0.315	23	0

### B. Data Pre-processing

Data Pre-processing is one of the important stages in data mining to improve the quality of datasets. This study focuses on dealing with unbalanced data contained in the diabetes dataset. The dataset used has 268 instances of negative diabetes and 500 instances of Positive Diabetes. The algorithms used to handle unbalanced data in the dataset are SMOTE (Synthetic Minority Oversampling Technique) and Smote-Tomeklink.

SMOTE is one of the most commonly used oversampling methods to solve the problem of data distribution imbalance in machine learning modeling. SMOTE aims to balance the distribution of classes by increasing the number of minority classes randomly by creating synthetic data for oversampling purposes [10]. Creating new data on the minority class using the equation (1).

$$Y' = Y^i + (Y^j - Y^i) * \gamma \quad (1)$$

$Y^i$  is the representation of the addition of the minority class.  $Y^i$  is the representation of minority class,  $Y^j$  is a value chosen at random from the k-nearest neighbors of the minority class on  $Y^i$ , and  $\gamma$  is a value in a randomly selected vector with a range of 0 to 1 [2]. SMOTE generates new synthesis training data by linear interpolation for the minority class. Synthesis training data is generated by randomly selecting one or more of the k-nearest neighbors for each sample in the minority class, as shown in Figure 2 below.

Tomeklink is an undersampling method that cleans noise data from the majority class with similar characteristics and overlapping[12]. Tomeklink eliminates the majority class instances closer to the minority class by applying the nearest neighbor rule to select instances. The combination of Tomeklink and Smote oversampling can improve accuracy better than individual performance [13].




Fig. 2 Process of Synthetic Minority Oversampling Technique (SMOTE) Algorithm [27]

### C. Random Forest Method

Random Forest is a decision tree-based ensemble learning method [28]. The Random Forest method has the advantages of

high accuracy, handling noise data, fast performance in training data, overfitting control, and easy implementation [26]. The working process of the Random Forest method in classifying data is shown in Figure 3.






Fig. 1 Working Process of Random Forest Method [26]

Figure 3 shows how the Random Forest algorithm works by creating a set of decision trees from a randomly selected subset, getting predictions from each decision tree, voting for each predicted outcome, and choosing the best prediction result based on the most votes assigned as the final prediction

#### D. Evaluation Performance

Performance testing uses a confusion matrix table. The confusion matrix is a table that is used to describe the performance of the classification method on a dataset whose true value is known. The confusion matrix can visualize the amount of data that is classified as true and false, as shown in Table III[29].

TABLE III  
CONFUSION MATRIX

Actual	Predicted	
	Negative	Positive
Negative	TN	FP
Positive	FN	TP

The formula used to calculate *accuracy* (6), *Sensitivity* (7), *Precision* (8) [30] [31][32], and *F1-score* (5)[33].

$$Accuracy = \frac{TP+TN}{TP+FN+TN+FP} \quad (6)$$

$$Sensitivity = \frac{TP}{TP+FN} \quad (7)$$

$$Precision = \frac{TP}{TP+FP} \quad (8)$$

$$F1 - score = \frac{2 \times precision \times recall}{precision + recall} \quad (9)$$

True Positive (TP) is a class of positive diabetes that is predicted correctly. False Positive (FP) is a diabetes-negative class but is predicted to be diabetes positive. True Negative (TN) is a diabetes negative class that is predicted correctly. False Negative (FN) is a positive diabetes class but is predicted to be diabetes negative.

### III. RESULT AND DISCUSSION

This research starts from the stages of data collection, data pre-processing, classification, and performance testing. The data used in this study is diabetes data obtained from Kaggle. The pre-processing of this study used the Smote and Smote-Tomeklink algorithms to deal with class imbalances in diabetes data. The classification method of this research is Random Forest. The performance test is based on accuracy, sensitivity, precision, and F1-score. The results of the comparison of the original data with the data from Smote and the results of Smote-Tomeklink are shown in Figure 4.




Fig. 4 Data Distribution Result

The classification method of this research is Random Forest. Performance testing is based on accuracy, sensitivity, precision, and F1-score using a confusion matrix table. Based on testing the Random Forest method using 10-fold cross-validation, the results obtained in the form of a confusion matrix table as shown in Table IV for the Random Forest method on the original data, Table V for the results of the Random Forest method with Smote, and Table VI for the results of the Random Forest method with Smote-Tomeklink. The results of the comparison of the performance of the Random Forest method as a whole are shown in Figure 5.

TABLE IV  
RESULT IN CONFUSION MATRIX OF RANDOM FOREST

Actual	Predicted	
	Negative	Positive
Negative	429	71
Positive	113	155

TABLE V  
RESULT IN CONFUSION MATRIX OF RANDOM FOREST AND SMOTE

Actual	Predicted	
	Negative	Positive

Negative	390	110
Positive	71	429

TABLE VI  
RESULT IN A CONFUSION MATRIX OF RANDOM FOREST AND SMOTE-TOMEKLINK

Actual	Predicted	
	Negative	Positive
Negative	385	90
Positive	56	419




Fig. 5 Result Performance of Classification Method

In Table IV, the Random Forest method succeeded in correctly classifying the negative class (TN) as many as 429 instances and the negative class classified incorrectly (FP) as many as 17 instances. While the correctly classified positive class (TP) is 155 instances, and the incorrectly classified positive class is 113 instances.

In Table V, the Random Forest method with Smote succeeded in correctly classifying the negative class (TN) in as many as 390 instances and the negative class classified incorrectly (FP) as many as 110 instances. While the positive class that is classified correctly (TP) is 429 instances, and the positive class that is classified incorrectly is 71 instances.

In Table VI, the Random Forest method with Smote-Tomeklink succeeded in correctly classifying the negative class (TN) in as many as 385 instances and the negative class classified incorrectly (FP) as 90 instances. While the positive class that is classified correctly (TP) is 419 instances and the positive class that is classified incorrectly is 56 instances.

Based on Figure 4, there was an increase in the performance of the Random Forest method with Smote-Tomeklink based on accuracy, sensitivity, precision, and F1-

score. In the original dataset, the Random Forest method has 76% accuracy, 57.8% sensitivity, 68.6% precision, and 62.7% F1-score. The Random Forest method with Smote has an accuracy of 81.9%, the sensitivity of 85.8%, precision of 79.6%, and F1-score of 82.6%. Meanwhile, using the Random Forest method with Smote-Tomeklink resulted in an accuracy of 86.4%, a sensitivity of 88.2%, a precision of 83.3%, and an F1-score of 85.1%.

Sensitivity has a very important role in improving the Accuracy and F1-score performance of the Random Forest method with Smote-Tomeklink. The Random Forest method with Smote-Tomeklink gives higher accuracy, sensitivity, precision, and F1-score results than smote and without sampling.

Random Forest method with Smote an increase in performance indicators Accuracy, sensitivity, precision, and F1-score. The increase in accuracy scores is 5.9%, Sensitivity is 28%, precision is 11%, and F1-score is 19.9%. The Random Forest method with Smote-Tomeklink showed an increase in the indicators of accuracy by 10.4%, Sensitivity by 30.4%, precision by 13.7%, and F1-score by 22.4%. Therefore, the

use of the Smote-Tomeklink method can increase accuracy, sensitivity, precision, and F1-score in the Random Forest method [11], [34], [35]. The comparison of the proposed method is better than previous studies, which can be shown in Table VII.

TABLE VII  
COMPARISON OF THE PROPOSED MODEL PERFORMANCE WITH PREVIOUS STUDIES

No	Author (Year)	Dataset	Method	Accuracy
1	[16]	Pima Indian Diabetes	KNN	83%
2	[17]	Pima Indian Diabetes	Decision Tree C.45	75.65%
3	[11]	Pima Indian Diabetes	SVM + K-Means Smote	82%
4	[21]	Pima Indian Diabetes	Logistic regression + Smote	82%
5	[22]	Pima Indian Diabetes	C4.5 Method + Smote	82%
6	<b>The Proposed Method</b>	<b>Pima Indian Diabetes</b>	<b>Random Forest + SMOTE Tomek links</b>	<b>86%</b>

#### IV. CONCLUSION

This study applies the Smote-Tomeklink algorithm to the Random Forest method for the classification of diabetes. The implementation of Smote-Tomeklink can improve the performance of accuracy, sensitivity, precision, and F1-score in the Random Forest method. The combination of Random Forest and Smote-Tomeklink got the best accuracy, sensitivity, and precision compared to Smote and without sampling for the classification of diabetes. There was an increase in performance indicators of 10.4% accuracy, 30.4% sensitivity, 13.7% precision, and 22.4 F1-score. Further research can apply Smote-Tomeklink to deal with the problem of data imbalance in multiclass data.

#### REFERENCES

[1] O. Heranova, "Synthetic Minority Oversampling Technique pada Averaged One Dependence Estimators untuk Klasifikasi Credit Scoring," *J. RESTI (Rekayasa Sist. dan Teknol. Informasi)*, vol. 3, no. 3, pp. 443–450, 2019, doi: 10.29207/resti.v3i3.1275.

[2] T. Zhu, Y. Lin, and Y. Liu, "Synthetic minority oversampling technique for multiclass imbalance problems," *Pattern Recognit.*, vol. 72, pp. 327–340, Dec. 2017, doi: 10.1016/j.patcog.2017.07.024.

[3] F. Last, G. Douzas, and F. Bacao, "Oversampling for Imbalanced Learning Based on K-Means and SMOTE," no. November, 2017.

[4] G. A. Pradipta, R. Wardoyo, A. Musdholifah, and I. N. H. Sanjaya, "Radius-SMOTE: A New Oversampling Technique of Minority Samples Based on Radius Distance for Learning from Imbalanced Data," *IEEE Access*, vol. 9, pp. 74763–74777, 2021, doi: 10.1109/ACCESS.2021.3080316.

[5] M. Kamaladevi, V. Venkataraman, and K. R. Sekar, "Tomek link Undersampling with Stacked Ensemble classifier for Imbalanced data classification," vol. 25, no. 4, pp. 2182–2190, 2021.

[6] W. C. Lin, C. F. Tsai, Y. H. Hu, and J. S. Jhang, "Clustering-based undersampling in class-imbalanced data," *Inf. Sci. (Nij.)*, vol. 409–410, pp. 17–26, 2017, doi: 10.1016/j.ins.2017.05.008.

[7] Z. Xu, D. Shen, T. Nie, and Y. Kou, "A hybrid sampling algorithm combining M-SMOTE and ENN based on Random Forest for medical

imbalanced data," *J. Biomed. Inform.*, p. 103465, 2020, doi: 10.1016/j.jbi.2020.103465.

[8] E. AT, A. M, A.-M. F, and S. M, "Classification of Imbalance Data using Tomek Link (T-Link) Combined with Random Under-sampling (RUS) as a Data Reduction Method," *Glob. J. Technol. Optim.*, vol. 01, no. S1, 2016, doi: 10.4172/2229-8711.s1111.

[9] Z. Wang, C. Wu, K. Zheng, X. Niu, and X. Wang, "SMOTETomek-Based Resampling for Personality Recognition," *IEEE Access*, vol. 7, pp. 129678–129689, 2019, doi: 10.1109/ACCESS.2019.2940061.

[10] N. V Chawla, K. W. Bowyer, and L. O. Hall, "SMOTE: Synthetic Minority Over-sampling TEchnique," *J. Artif. Intell. Res.*, vol. 16, pp. 341–378, 2002.

[11] H. Hairani, K. E. Saputro, and S. Fadli, "K-means-SMOTE for handling class imbalance in the classification of diabetes with C4.5, SVM, and naive Bayes," *J. Teknol. dan Sist. Komput.*, vol. 8, no. 2, pp. 89–93, 2020, doi: 10.14710/jtsiskom.8.2.2020.89-93.

[12] I. Tomek, "Tomek Link: Two Modifications of CNN," *IEEE Trans. Syst. Man Cybern.*, pp. 769–772, 1976.

[13] E. F. Swana, W. Doorsamy, and P. Bokoro, "Tomek Link and SMOTE Approaches for Machine Fault Classification with an Imbalanced Dataset," *Sensors*, vol. 22, no. 9, 2022, doi: 10.3390/s22093246.

[14] A. Alzahrani and A. Safhi, "The role of data mining techniques and tools in big data management in healthcare field," *Sustain. Eng. Innov.*, vol. 4, no. 1, pp. 58–65, 2022, doi: 10.37868/sci.v4i1.id128.

[15] S. Sarač and B. Duraković, "Analysis of student performances in online and face-to-face learning: A case study from a Bosnian public university," *Herit. Sustain. Dev.*, vol. 4, no. 2, pp. 87–94, 2022, doi: 10.37868/HSD.V4I2.91.

[16] R. Kaur, "Predicting diabetes by adopting classification approach in data mining," *Int. J. Informatics Vis.*, vol. 3, no. 2–2, pp. 218–221, 2019, doi: 10.30630/joiv.3.2-2.229.

[17] A. Azrar, M. Awais, Y. Ali, and K. Zaheer, "Data mining models comparison for diabetes prediction," *Int. J. Adv. Comput. Sci. Appl.*, vol. 9, no. 8, pp. 320–323, 2018, doi: 10.14569/ijacsa.2018.090841.

[18] S. Barik, S. Mohanty, S. Mohanty, and D. Singh, "Analysis of prediction accuracy of diabetes using classifier and hybrid machine learning techniques," *Smart Innov. Syst. Technol.*, vol. 153, no. January, pp. 399–409, 2021, doi: 10.1007/978-981-15-6202-0\_41.

[19] H. Hairani, M. Innuddin, and M. Rahardi, "Accuracy Enhancement of Correlated Naive Bayes Method by Using Correlation Feature Selection (CFS) for Health Data Classification," in *2020 3rd International Conference on Information and Communications Technology (ICOIACT)*, Nov. 2020, pp. 51–55, doi: 10.1109/ICOIACT50329.2020.9332021.

[20] C. Fiarni, E. M. Sipayung, and S. Maemunah, "Analysis and prediction of diabetes complication disease using data mining algorithm," *Procedia Comput. Sci.*, vol. 161, pp. 449–457, 2019, doi: 10.1016/j.procs.2019.11.144.

[21] Erlin, Y. N. Marlim, Junadhi, L. Suryati, and N. Agustina, "Early Detection of Diabetes Using Machine Learning with Logistic Regression Algorithm," *J. Nas. Tek. Elektro dan Teknol. Inf.*, vol. 11, no. 2, pp. 88–96, 2022.

[22] C. Azad, B. Bhushan, R. Sharma, A. Shankar, K. K. Singh, and A. Khamparia, "Prediction model using SMOTE, genetic algorithm and decision tree (PMSGD) for classification of diabetes mellitus," *Multimed. Syst.*, vol. 28, no. 4, pp. 1289–1307, 2022, doi: 10.1007/s00530-021-00817-2.

[23] X. Shi, T. Qu, G. Van Pottelbergh, M. van den Akker, and B. De Moor, "A Resampling Method to Improve the Prognostic Model of End-Stage Kidney Disease: A Better Strategy for Imbalanced Data," *Front. Med.*, vol. 9, no. March, pp. 1–9, 2022, doi: 10.3389/fmed.2022.730748.

[24] K. Wang *et al.*, "Improving risk identification of adverse outcomes in chronic heart failure using smote +enn and machine learning," *Risk Manag. Healthc. Policy*, vol. 14, no. May, pp. 2453–2463, 2021, doi: 10.2147/RMHP.S310295.

[25] H. Kaur, H. S. Pannu, and A. K. Malhi, "A systematic review on imbalanced data challenges in machine learning: Applications and solutions," *ACM Computing Surveys*, vol. 52, no. 4. Association for Computing Machinery, pp. 1–34, Aug. 2019, doi: 10.1145/3343440.

[26] K. Guo, X. Wan, L. Liu, Z. Gao, and M. Yang, "Fault diagnosis of intelligent production line based on digital twin and improved random forest," *Appl. Sci.*, vol. 11, no. 16, pp. 1–18, 2021, doi: 10.3390/app11167733.

[27] J. Chen, H. Huang, A. G. Cohn, D. Zhang, and M. Zhou, "Machine learning-based classification of rock discontinuity trace: SMOTE oversampling integrated with GBT ensemble learning," *Int. J. Min. Sci.*

- Technol.*, vol. 32, no. 2, pp. 309–322, 2021, doi: 10.1016/j.ijmst.2021.08.004.
- [28] Y. Sun, H. Zhang, T. Zhao, Z. Zou, B. Shen, and L. Yang, “A New Convolutional Neural Network with Random Forest Method for Hydrogen Sensor Fault Diagnosis,” *IEEE Access*, vol. 8, pp. 85421–85430, 2020, doi: 10.1109/ACCESS.2020.2992231.
- [29] H. Hartono and E. Ongko, “Avoiding Overfitting dan Overlapping in Handling Class Imbalanced Using Hybrid Approach with Smoothed Bootstrap Resampling and Feature Selection,” *Int. J. Informatics Vis.*, vol. 6, no. June, pp. 343–348, 2022.
- [30] H. Hairani, A. Anggrawan, A. I. Wathan, K. A. Latif, K. Marzuki, and M. Zulfikri, “The Abstract of Thesis Classifier by Using Naive Bayes Method,” in *Proceedings - 2021 International Conference on Software Engineering and Computer Systems and 4th International Conference on Computational Science and Information Management, ICSECS-ICCSIM 2021*, 2021, no. August, pp. 312–315, doi: 10.1109/ICSECS52883.2021.00063.
- [31] A. Luque, A. Carrasco, A. Martín, and A. de las Heras, “The impact of class imbalance in classification performance metrics based on the binary confusion matrix,” *Pattern Recognit.*, vol. 91, pp. 216–231, 2019, doi: 10.1016/j.patcog.2019.02.023.
- [32] H. Qteat and M. Awad, “Using Hybrid Model of Particle Swarm Optimization and Multi-Layer Perceptron Neural Networks for Classification of Diabetes,” *Int. J. Intell. Eng. Syst.*, vol. 14, no. 3, pp. 11–22, 2021, doi: 10.22266/ijies2021.0630.02.
- [33] H. Hanafi, A. H. Muhammad, I. Verawati, and R. Hardi, “An Intrusion Detection System Using SDAE to Enhance Dimensional Reduction in Machine Learning,” *Int. J. Informatics Vis.*, vol. 6, no. June, pp. 306–316, 2022.
- [34] H. Hairani, A. S. Suweleh, and D. Susilowaty, “Penanganan Ketidak Seimbangan Kelas Menggunakan Pendekatan Level Data,” *MATRIK J. Manajemen, Tek. Inform. dan Rekayasa Komput.*, vol. 20, no. 1, pp. 109–116, 2020, doi: 10.30812/matrik.v20i1.846.
- [35] M. Y. Thanoun, M. T. Yaseen, and A. M. Aleesa, “Development of Intelligent Parkinson Disease Detection System Based on Machine Learning Techniques Using Speech Signal,” *Int. J. Adv. Sci. Eng. Inf. Technol.*, vol. 11, no. 1, pp. 388–392, 2021.